

ACRYLIC

Water Based Emulsion Polish

DESCRIPTION: **ACRYLIC** is a semi-buffable, fast drying polish, which offers a good durable finish that is designed to combat scuff marking.

Acrylic dries to a high sheen, which can be increased by burnishing if required. It is ideal for use on coated wood or Granwood and is also suitable for thermoplastic, vinyl, linoleum and rubber flooring.

APPLICATION: Before applying Acrylic, ensure the surface is clean and thoroughly dry. Some sealed surfaces may need to be lightly abraded to form a 'key' for polish to adhere.

Apply Acrylic evenly using a suitable applicator or mop. It is recommended that the first coat of polish is kept approximately 6 inches away from the edge of the floor to prevent build-ups. When initial coat is dry (approximately 45 minutes) apply second coat at a right angle to the first, ensuring all floor surface is covered. The polish film will harden for several hours after drying. For maximum results, the floor should be left as long as possible before use, preferably overnight.

MAINTENANCE: Floors should be swept daily. As and when necessary, the floor should be damp mopped or spray cleaned using a solution of **JADEx** or **SPEEDKLEEN** to remove heavier soiling. When dry, the floor may then be burnished if required using a suitable machine and appropriate grade of floor maintenance pad.

After a period of time, it may be necessary to strip off any old polish and dirt. This can easily be done using a warm water solution of **SWIFT** hard surface cleaner, in conjunction with a standard speed rotary machine and green floor maintenance pad.

NOTE: Care should be taken when damp mopping or machine scrubbing wooden floors. It is recommended to use minimum amount of water and, where applicable, ensure any residual moisture is removed quickly to minimise the possibility of damage or swelling of the wood through water penetration.

COVERAGE: Approximately 200 – 250m² per 5 litre (1 coat)

PACK SIZE: 5 litre containers (4 x 5 litre case) and 1 litre containers (6 x 1 litre case)

STORAGE: Store in a cool, dry place and protect from frost.

HEALTH & SAFETY: For full health and safety information, please refer to our Material Health & Safety Data Sheet.

No liability is accepted for any loss or damage arising directly from the use of the Company's products or from the use of the information given in its publications. Prospective users should therefore satisfy themselves by appropriate trials that the product to be used is suitable for the intended use.

GRANWAX PRODUCTS LIMITED
WEST STREET
RIDDINGS
ALFRETON
DERBYSHIRE DE55 4EW
Telephone: 01773 541177
Fax: 01773 541429
Email: info@granwax.com
Website: www.granwax.com