

360 FAST SET

Solid Cure Wood Floor Adhesive

Description: A solvent based, fast setting adhesive for wood flooring.

Suitable for installation of :

- Finger parquet
- Mosaic panels
- Mosaic parquet
- Solid strip flooring (up to 55 x 250mm, minimum 10mm thickness)
- Multiple layer engineered wood flooring: individual block (max 70 x 600mm)
- Unfinished wood strip (max 75 x 600mm, min 14mm thickness)
- Possible use for re-adhering old blocks (stuck with Bitumen). **MUST TRIAL BEFORE FULL USE**

Preparation: Prior to processing the subfloor must be checked according to British Standard or corresponding national standards. The subfloor should be sound and free of cracks. Subfloors must have sufficient surface strength, be permanently dry, level, clean and free of contaminants, which will affect adhesion. In addition, porosity and grip of surface need to be checked. Moisture level, room temperature, subfloor temperature and air humidity readings must be taken using a recommended meter prior to application.

It must be determined that the subfloor is sufficiently prepared, if necessary mechanical pre-treatment of the subfloor, ie. vacuuming, sweeping, mechanical brushing, sanding, etc., should be performed depending on the condition of the subfloor. All cracks and joints, except expansion joints, must be properly repaired. Uneven subfloors can be levelled with **Granwax Base** or **Rapid Base** levelling compounds.

Application: Apply **Granwax 360 Fast Set Adhesive** to subfloor using an appropriate notched trowel. Avoid adhesive pooling and excessive layer thickness by evenly raking the notched trowel over adhesive layer. Install wood flooring during specified open time, slide in and press down firmly.

It is recommended that any adhesive residues are quickly removed whilst wet. Adhesive residues left to cure on the surface of the wood may result in mechanical sanding being required to remove the residual adhesive, thereby possibly damaging the surface of the flooring.

Please note: *This product contains solvents that will develop easily flammable and volatile vapours during handling and application. These vapours can turn into an extremely explosive mixture. Keep the working area well ventilated at all times. Do not use this product anywhere close to open fires, lights, smoke or welding sparks. Any and all previously used electrical appliances on site need to be turned off in time to cool down completely before using this product. Prevent the build up of static electricity and avoid electrical sparks from light switches, tools or appliances. Prior to floor installation, display visible warning signs at a sufficient distance from the work area, "Warning! Explosive materials. No smoking or open fire".*

Floor Sanding: Floors laid using 360 Fast Set are ready for machine sanding after approx. 72 hours

Pack Size: 17kg metal bucket

Coverage: Approximately 1kg per m² (subfloor and trowel size dependent)

Open time: Approximately 10 minutes at 20°C

Pot Life: Approximately 40 minutes at 20°C

Shelf Life: In original sealed container – minimum 12 months (not sensitive to frost)

Health & Safety: For full health and safety information, please see the product Material Safety Data Sheets. .

The information provided herein is correct to the best of our knowledge. No liability for any errors or opinions is accepted. You should satisfy yourself before applying any of the information contained herein to your particular circumstances. Granwax Products Limited can accept no responsibility for any loss as a result of any person placing reliance on any information contained herein.

GRANWAX PRODUCTS LIMITED

WEST STREET

RIDDINGS, ALFRETON

DERBYSHIRE DE55 4EW

Telephone: 01773 541177 Fax: 01773 541429

Email: info@granwax.com Website: www.granwax.com

April 2011