

360 PRIMER

Description: A clear drying, solvent based primer for use with **Granwax 360 Fast Set Adhesive**. Improves bond strength and prevents residual moisture contamination of wood flooring. Suitable for plank, block and parquet flooring. Also highly recommended for use on floors with under-floor heating.

Preparation: Prior to processing the sub floor must be checked according to British Standard or corresponding national standards. The sub floor should be sound and free from cracks. Subfloors must have sufficient surface strength, be permanently dry, level clean and free from contaminants which will affect adhesion. In addition, porosity and grip of surface need to be checked. Moisture level, room temperature, subfloor temperature and air humidity readings must be taken using a recommended meter prior to application.

It must be determined that the subfloor is sufficiently prepared, if necessary mechanical pre-treatment of the subfloor, i.e. vacuuming, sweeping, mechanical brushing, sanding, etc., should be performed depending on the condition of the subfloor. All cracks and joints, except expansion joints, must be properly repaired. Uneven subfloors can be levelled with **Granwax Base** or **Rapid Base** levelling compounds.

Application: Ensure adequate ventilation at all times. Do not dilute. Apply one coat with suitable **Granwax Roller** (brush may be used if required). Avoid puddles and accumulations of the product. Product will soak into porous, absorbent subfloors and create a closed film on dense, non absorbent subfloor. Will dry clear.

Please note: *This product contains solvents that will develop easily flammable and volatile vapours during handling and application. These vapours can turn into an extremely explosive mixture. Keep the working area well ventilated at all times. Do not use this product anywhere close to open fires, lights, smoke or welding sparks. Any and all previously used electrical appliances on site need to be turned off in time to cool down completely before using this product. Prevent the build up of static electricity and avoid electrical sparks from light switches, tools or appliances. Prior to floor installation, display visible warning signs at a sufficient distance from the work area, "Warning! Explosive materials. No smoking or open fire".*

Pack Size: 8kg metal can

Coverage: Approximately 4m² per kg when applied by Granwax PU Resin Roller

Drying time: Approximately 30 minutes at 20°C

Shelf Life: In original sealed container – minimum 12 months

Health & Safety: For full health and safety information, please see the product Material Safety Data Sheet

The information provided herein is correct to the best of our knowledge. No liability for any errors or opinions is accepted. You should satisfy yourself before applying any of the information contained herein to your particular circumstances. Granwax Products Limited can accept no responsibility for any loss as a result of any person placing reliance on any information contained herein.

GRANWAX PRODUCTS LIMITED
WEST STREET
RIDDINGS
ALFRETON
DERBYSHIRE
DE55 4EW
Telephone: 01773 541177
Fax: 01773 541429
Email: info@granwax.com
Website: www.granwax.com

April 2011