

GRANWAX HARD WAX OIL

RECOMMENDED APPLICATION FOR WORKSURFACES

DESCRIPTION: A blend of natural oils & waxes offering exceptional durability and resistance for wooden kitchen worktops, work surfaces and areas subjected to a high degree of wear. Produces a water repellent finish. Easy application with no sanding between coats. To maintain and renovate simply re-apply.

PREPARATION: Ensure all surfaces are clean, dry and free from any previous finish. Sand with fine grade sanding paper and remove all dust carefully.

APPLICATION: **FIRST COAT**

Ensure all areas to be coated are extremely well ventilated during and after application.

Stir contents thoroughly before and during use and apply in a warm, well ventilated room. Apply THINLY using a good quality bristle or synthetic brush and lay EVENLY, following the direction of the grain. Remove any surplus material immediately with a cloth, carefully checking all areas for any excess application. Leave to dry 8 – 10 hours, or preferably overnight with good ventilation.

SECOND COAT

Apply as first coat, THINLY, allowing good ventilation. Leave to dry overnight. When the surface area is completely dry, a light buff with further enhance the sheen level.

- NOTES:**
- 1) Ensure all areas to be coated are extremely well ventilated during and after application has occurred.
 - 2) Certain dense or oily substrates may only require a single application and subsequently buffed to achieve the desired finish.
 - 3) If either coat is applied heavily, drying time will be significantly increased.
 - 4) Longer drying periods may occur depending on site conditions. Extremes of temperature and damp conditions should be avoided at all times during application.
 - 5) Always apply sparingly and remove any excess product thoroughly.

COLOURS: Clear, Onyx, White, Whiskey, Antique

SHEEN LEVELS: Clear – Satin/Matt and Ultra Matt Coloured: Satin/Matt

COVERAGE: A single application will cover approximately 12 – 15m² per litre, depending on the density of the substrate.

PACK SIZE: 1 litre, 2.5 litre, & 5 litre containers (Clear) 1 litre & 2.5 litres (Coloured)

STORAGE: Store in cool, dry place. Protect from frost. Temperatures below 10°C and above 40°C should be avoided. Shelf Life: 12 months from date of dispatch (unopened containers).

HEALTH & SAFETY: For product health and safety information, please refer to our Material Health & Safety Data Sheet.

The information provided herein is correct to the best of our knowledge. No liability for any errors or opinions is accepted. You should satisfy yourself before applying any of the information contained herein to your particular circumstances. Granwax Products Limited can accept no responsibility for any loss as a result of any person placing reliance on any information contained herein.

GRANWAX PRODUCTS LIMITED

WEST STREET

RIDDINGS, ALFRETON

DERBYSHIRE DE55 4EW

Telephone: 01773 541177 Fax: 01773 541429

Email: info@granwax.com Web: www.granwax.com