

# MATERIAL SAFETY DATA SHEET



Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: September 2009

Reviewed by MC

## 1. Identification of substance

Substance: **MS Flex Wood Floor Adhesive** Supplier: Granwax Products Limited  
West Street  
Riddings, Alfreton  
Derbyshire DE55 4EW  
Telephone: 01773 541177 Fax: 01773 541429  
This revision: June 2009

## 2. Composition/Data on components

*Composition and classification of potentially hazardous components.*

<u>Component</u>	<u>Concentration range</u>	<u>Classification</u>	<u>Risk Phrase</u>
Di isononylphthalates 28553-12-0	2.5 – 10%		

## 3. Hazards identification

None applicable

# MATERIAL SAFETY DATA SHEET



Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: June 2009

Reviewed by MC

## 4. First aid measures

**Skin exposure:** immediately wash the affected area with soap or mild detergent and water. Remove contaminated clothing. If symptoms persist seek medical advice.

**Eye splashes:** If the material is splashed into the eye, wash the affected eye with clean running water for at least 15 minutes. Seek medical advice.

**Swallowing (ingestion):** If material is accidentally swallowed, do not make patient vomit, seek medical advice. This information should be taken with the patient when seeking medical advice.

**Inhalation;** Move patient to fresh air. If patient is unconscious, place in the recovery position and seek medical help immediately. Do not give patient anything to drink.

**CALL FOR MEDICAL ASSISTANCE IF YOU FEEL UNWELL**

## 5. Fire fighting measures

CO2 or foam extinguishants

No special requirements.

## 6. Accidental release measures

Spillages should be contained with a non-combustible absorbent material and collected for disposal in accordance with the local regulations.

Spillages should not be allowed to run to surface waters . PPE must be worn.

## 7. Handling & storage

No special requirements

All chemical preparations should be stored securely where they cannot be interfered with or used by unauthorised persons.



**GRANWAX**  
Products Limited

# MATERIAL SAFETY DATA SHEET

Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: June 2009

Reviewed by MC

## Exposure controls & personal protection

No special requirements

## 9. Physical and chemical properties

Appearance:	Pasty beige	Odour	Characteristic
pH:	Not Applicable	Boiling point / range:	NA
Melting point / range	Undetermined	Flash point:	NA
Flammability	Non Flammable	Autoflammability:	Not applicable
Explosive properties	Not applicable	Oxidising properties:	none
Vapour pressure	Not applicable	Relative density:	Approx. 1.55g/cm <sup>3</sup>
Solubility	not miscible	Partition coefficient: n-octanol / water	Not determined
Solvent Content	0%	Solids Content	60%

## 10. Stability and reactivity

Product generally stable

## 11. Toxicological information

This product is of generally low toxicity

## 12. Ecological information

Class WKG1 Slight water hazard.

## 13. Disposal considerations

This product is not classified as Harmful/Flammable. Any surplus or waste arising from the normal use of this product must be disposed of in accordance with the local waste regulations.

# MATERIAL SAFETY DATA SHEET



Product name: **MS Flex Wood Floor Adhesive**

Reviewed date: June 2009

## 14. Transport information

Not classified as a hazard

## 15. Regulatory information

None

## 16. Other information

No other safety information is applicable to the use of this preparation for its intended purpose