



**GRANWAX**  
Products Limited

# MATERIAL SAFETY DATA SHEET

Product name: **PU resin primer**

Reviewed date: September 2009

Reviewed by MC

## 1. Identification of substance

Substance: **Pu resin primer**  
Supplier: Granwax Products Limited  
West Street  
Riddings, Alfreton  
Derbyshire DE55 4EW  
Telephone: 01773 541177 Fax: 01773 541429  
This revision: June 2009

## 2. Composition/Data on components

*Composition and classification of potentially hazardous components.*

<u>Component</u>	<u>Concentration range</u>	<u>Classification</u>	<u>Risk Phrase</u>
Diphenylmethanediisocyanate, Isomers and homologues 9016-87-9	2.5 -10%	Xn,Xi	R20-36/37/ R38-40-42 R 43-48/20
Danger Health Hazard 3.4 r/1 3.2'2, 3.3/2, 3.4.S/1			

## 3. Hazards identification

Xn Harmful

Risk Phrases: R36/37/38 Irritating to eyes, respiratory system and skin.  
R42/43 May cause sensitisation by inhalation and skin contact  
Contains isocyanates: see information provided by the manufacturer.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H315 Causes skin irritation  
H319 Causes serious eye irritation  
H319 May cause allergic skin reaction  
H335 May cause respiratory irritation  
Contains isocyanates may cause an allergic reaction.

# MATERIAL SAFETY DATA SHEET



Product name: **PU resin primer**

Reviewed date: September 2009

Reviewed by MC

## 4. First aid measures

**Skin exposure:** immediately wash the affected area with soap or mild detergent and water. Remove contaminated clothing. If symptoms persist seek medical advice. Prolonged or repeated contact may cause short term irritation, and could cause dermatitis.

**Eye splashes:** If the material is splashed into the eye, wash the affected eye with clean running water for at least 15 minutes. Seek medical advice.

**Swallowing (ingestion):** If material is accidentally swallowed, do not make patient vomit, seek medical advice. This information should be taken with the patient when seeking medical advice.

**Inhalation;** Move patient to fresh air. If patient is unconscious, place in the recovery position and seek medical help immediately. Do not give patient anything to drink.

**CALL FOR MEDICAL ASSISTANCE IF YOU FEEL UNWELL**

## 5. Fire fighting measures

Use dry powder, CO<sub>2</sub> or foam.

This material is **FLAMMABLE** and will produce smoke containing hazardous combustion products.

## 6. Accidental release measures

Spillages should be contained with a non-combustible absorbent material and collected for disposal in accordance with the local regulations. Do not place in sealed containers.

Spillages should not be allowed to run to surface waters. PPE must be worn.

## 7. Handling & storage

Store in a cool, well ventilated area.

Keep container tightly sealed

All chemical preparations should be stored securely where they cannot be interfered with or used by unauthorised persons.

# MATERIAL SAFETY DATA SHEET



Product name: **PU resin primer**

Reviewed date: September 2009

Reviewed by MC

## Exposure controls & personal protection

9016-87-9 diphenylmethandiisocyanate, isomers and homologues

WEL Short term value 0.07 mg/m<sup>3</sup>  
Long term value 0.02 mg/m<sup>3</sup>  
Sen: as- NCO

### Personal Protective Equipment

Use respiratory protection at all times. If exposure prolonged wear self contained respiratory protective device.

Use tightly sealed protective goggle.

Wear Butyl Hand protection.

Wear suitable overalls.

### Hygiene:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work

Avoid contact with eyes and skin

Do not inhale gases/fumes/vapours



**GRANWAX**  
Products Limited

# MATERIAL SAFETY DATA SHEET

Product name: **PU resin primer**

Reviewed date: September 2009

## 9. Physical and chemical properties

Appearance:	Fluid	Odour	Characteristic
pH:	Not Applicable	Boiling point / range:	190 deg.C
Melting point / range	Undetermined	Flash point:	Not applicable
Flammability	Non Flammable	Autoflammability:	Not applicable
Explosive properties	Not applicable	Oxidising properties:	none
Vapour pressure	220 hPA	Relative density:	Approx. 1.14g/cm <sup>3</sup>
Solubility	not miscible	Partition coefficient: n-octanol / water	Not determined
Solvent Content	0%	Solids Content	59%

## 10. Stability and reactivity

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.  
Dangerous Reaction: No dangerous reactions known.  
Dangerous decomposition products: No dangerous decomposition products known.

## 11. Toxicological information

Acute Toxicity:  
Irritant to skin and mucous membranes and to the eyes.  
Sensitization possible through inhalation and /or skin contact  
Harmful  
Irritant

## 12. Ecological information

Class WKG1 Slight water hazard.

## 13. Disposal considerations

This product is classified as Harmful/Flammable. Any surplus or waste arising from the normal use of this product must be disposed of in accordance with the local special waste regulations.



**GRANWAX**  
Products Limited

# MATERIAL SAFETY DATA SHEET

Product name: **PU resin primer**

Reviewed date: September 2009

## 14. Transport information

Not classified as a hazard

## 15. Regulatory information

Code Letter and hazard designation: Xn Harmful

Risk Phrases: R36/37/38 Irritating to eyes, respiratory system, and eyes.  
R42/43 may cause sensitization by inhalation and skin contact

Safety Phrases: S23 Do not breathe vapours, S24 Avoid contact with skin, S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice, S37 wear suitable gloves, S45 In case of accident or if you feel unwell seek medical advice showing this container or label.

S60 This material must be disposed of as hazardous waste.

## 16. Other information

No other safety information is applicable to the use of this preparation for its intended purpose