

WOOD FLOOR DYE

GRANWAX WOOD FLOOR DYE is a solvent based wood dye formulated to offer exceptional depth of colour on all interior wood surfaces. Granwax Wood Floor Dyes are quick drying and easy to apply, usable with all water and white spirit borne Granwax finishes.* (Not suitable for use with Granguard or Granstone). Granwax Wood Floor Dyes are recommended for use on wood floors, but may also be used on other wood surfaces and products, such as doors, furniture and panelling.

** Always trial before use to satisfy yourself of acceptable results. Be aware that variations in wood and finishing techniques will alter the final appearance. Do not mix dyes with finishes.*

PREPARATION

Sand the floor in stages following standard procedure, finishing on a fine (120 grit) grade. Always sand the floor in the direction of the grain pattern where possible, ensuring the removal of any blemishes and glue residue prior to the application of Granwax Wood Floor Dyes. Take care to remove all traces of sanding dust and test the chosen Granwax Wood Floor Dye on a similar substrate to verify colour/shade.

Mix the contents well and always check the shade before application.

APPLICATION

Take a clean brush, lint free cotton cloth or sponge and apply in the direction of the wood grain where possible. Take care to remove any excess stain immediately with a separate, clean absorbent cloth, again following the direction of the grain pattern. To obtain a uniform colour, always wipe evenly, blending the stain over the whole surface by exerting a degree of pressure when applying by hand.

Leave to dry and do not sand between coats.

The application of additional coats will deepen the existing colour/shade.

DRYING TIME:

10 - 15 minutes at room temperature

OVERCOAT TIME:

Approximately 1 hour

COVERAGE:

16m² per litre (depending on substrate and method of application)

THINNERS:

Granwax Polysolve

PACK SIZE:

5 litre containers

COLOUR SHADES:

Rich Mahogany, Light Oak, Medium Oak, Dark Oak, Jacobean Oak, Antique Pine, Teak

The information provided herein is correct to the best of our knowledge. No liability for any errors or opinions is accepted. You should satisfy yourself before applying any of the information contained herein to your particular circumstances. Granwax Products Limited can accept no responsibility for any loss as a result of any person placing reliance on any material contained herein.

GRANWAX PRODUCTS LIMITED

WEST STREET

RIDDINGS, ALFRETON

DERBYS, DE55 4EW

Telephone: 01773 541177

Fax: 01773 541429

Email: info@granwax.com

Web: www.granwax.com